

### ▶ **PRODUCT BRIEF**

**13G black HPPE/steel/basalt liner with black foam sandy nitrile palm coating, reinforcement in the thumb crotch**

- ✓ Excellent fit and dexterity.
- ✓ level F heavy cut protection.
- ✓ Sandy foam nitrile coating for better grip in dry, wet and oily conditions
- ✓ Excellent abrasion resistance
- ✓ Reinforcement at thumb crotch can extend the life of usage.



### ▶ **COATING**

<b>Color</b>	Black
<b>Material</b>	Nitrile
<b>Texture</b>	Sandy Foam
<b>Area</b>	Palm coated

### ▶ **LINER**

<b>Gauge</b>	13
<b>Color</b>	Black
<b>Material</b>	HPPE/steel/basalt

### ▶ **EN Test Results**

<b>Test</b>	Result
<b>EN 388:2016</b>	4X43F
<b>Abrasion</b>	>8000 Cycles
<b>Cut</b>	X
<b>Tear</b>	>75 N
<b>Puncture</b>	>100 N
<b>EN ISO13997</b>	>30 N
<b>ANSI CUT</b>	A6

### ▶ **Dimensions**

Size	Weight (g/pair) (±5%)	Length(mm)		Width(mm)	
		Glove (-5/+10)	Wrist (±5)	Palm (±5)	Wrist (±5)
7"	65.5	225	74	87	75
8"	73	235	77	94	77
9"	80.5	245	80	99	80
10"	86.5	255	84	104	83
11"	94.5	265	87	107	86
12"	100	275	90	109	89

### ▶ **Features**

-  Strong grip
-  Cut Resistance
-  High-abrasion
-  Flexibility
-  Reinforced thumb area

### ▶ **Applications**

-  Construction
-  Mechanical Processing
-  Facility maintenance
-  Transportation & Warehousing
-  Glass & Metal Handling